

# HATHORN CAMERA REELS

**STANDARD**



**Get A Quote**

**PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA**



For use with  
Hathorn  
Command  
Modules



Self-Levelling  
Camera Heads



200 ft to 500  
ft of Push Rod



512Hz or  
640Hz High  
Power Sonde



Industry-Leading  
Warranty

Hathorn® camera reels are designed to work with any Hathorn control module, past present or future. These rugged and durable camera reels come fitted with your choice of Hathorn self-levelling camera heads, all equipped with super-bright, cool running LEDs for optimal picture quality. Butt-welded steel frame construction, stainless steel camera heads and your choice of cable size allow you to push further than ever before and remain in the field longer with Hathorn's legendary reliability.

Hathorn camera reels are trusted by plumbers, municipalities, general contractors, home inspectors, petrochemical companies, and mining engineers to deliver a clear, recordable video inspection every time the camera is used. Designed and manufactured in North America, with a full one-year warranty.

# HATHORN CAMERA REELS

**STANDARD**

**PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA**



## Specifications

### Display

**Size & Type** Compatible with all Hathorn control modules. H12+ recommended for best picture and options

### Features

**Sonde Frequency** High power 512Hz or 640Hz (available only with H12+ controller)

**Push Rod** HDPE push rod with coax core - multiple lengths and thicknesses

### Weight & Dimensions

**Weight** See specific item in list to the right

**Dimensions (L x W x H)** See specific item in list to the right

### Environmental

**Water Resistance - Camera & Rod** IP67 to 60psi

**Water Resistance - Battery Cradle** IP65

**Water Resistance - Reel Hub** IP64

**Operating Temperature** 14°F to 122°F (-10°C to 50°C)

**Storage Temperature** -4°F to 140°F (-20°C to 60°C)

Extra Large		Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
<b>Catalog #</b>									
XLR-5568-SL	1.68"	✓	500 ft.	5/8"	3"	90lbs.	12"	33" x 29" x 16"	
XLR-5168-SL	1.68"	✓	500 ft.	1/2"	3"	75lbs.	12"	33" x 29" x 16"	

Large		Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
<b>Catalog #</b>									
LR-3168-SL	1.68"	✓	300 ft.	1/2"	3"	55 lbs.	12"	33" x 29" x 16"	
LR-2168-SL	1.68"	✓	200 ft.	1/2"	3"	45 lbs.	12"	33" x 29" x 16"	
LR-4143-SL	1.43"	✓	400 ft.	1/2"	3"	65 lbs.	10"	33" x 29" x 16"	
LR-3143-SL	1.43"	✓	300 ft.	1/2"	3"	55 lbs.	10"	33" x 29" x 16"	
LR-2143-SL	1.43"	✓	200 ft.	1/2"	3"	45 lbs.	10"	33" x 29" x 16"	

Mid		Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
<b>Catalog #</b>									
MR-2168-SL	1.68"	✓	200 ft.	1/2"	3"	42 lbs.	12"	29" x 18" x 15"	
MR-2143-SL	1.43"	✓	200 ft.	1/2"	3"	42 lbs.	10"	29" x 18" x 15"	
MR-2123-SL	1.23"	✓	200 ft.	400"	2"	42 lbs.	6"	29" x 18" x 15"	

Mini		Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
<b>Catalog #</b>									
MN-2123-SL	1.23"	✓	200 ft.	1/2"	2"	33 lbs.	6"	24" x 18" x 10"	
MN-2100	1.23"	✗	200 ft.	3/8"	1.5"	33 lbs.	4"	24" x 18" x 10"	

\*Straight View Cameras Available

