

# RIDGID®

## SeeSnake® rM200 Camera Reel Series with TruSense®



The new RIDGID® SeeSnake® rM200 Camera Reel Series now features TruSense® technology for superior image clarity and camera functionality. Already known for its built-in versatility and portability, the rM200 series, now also has enhanced transportation and storage features. The interchangeable D2 Series Drums (D2A & D2B) provide various combinations of cable stiffness and spring flexibility to tackle any inspection job.

- **Enhanced camera functionality** – TruSense technology with High Dynamic Range (HDR) sensor and TiltSense™ inclinometer give crisp, always upright images and feedback on camera angle in-pipe
- **Interchangeability** – Easily interchangeable D2 drums for on-the-job flexibility and compatible with all SeeSnake monitors
- **Pushability** – Drums feature different push cable lengths, diameters, stiffness and springs for customized jobs
- **Portability** – Multi-functional pull handle and smooth wheels for easy transport and positioning
- **Increased storage** – New taller stow bins with increased internal capacity to store



**rM200A Reel**  
Catalog No. 63658



**rM200B Reel**  
Catalog No. 63663

## SPECIFICATIONS

	<b>rM200A</b>	<b>rM200B</b>
• Length.....	21.0" (535 mm)	21.0" (535 mm)
• Width.....	13.6" (345 mm)	13.6" (345 mm)
• Height.....	24" (610 mm)	24" (610 mm)
• Drum Diameter.....	17" (432 mm)	17" (432 mm)
• Camera		
Diameter.....	1" (25 mm)	1" (25 mm)
Type.....	Self-leveling w/TruSense	Self-leveling w/TruSense
Resolution.....	640 x 480	640 x 480
• Spring Assembly		
Type.....	Single	Dual Nested
Length.....	12.4" (316 mm)	17.1" (435 mm)
• Line Capacity.....	1.5" – 8" (38 mm – 203 mm)	2" – 8" (51 mm – 203 mm)
• Push Cable		
Length.....	200' (61 m)	165' (50 m)
Diameter.....	0.3" (7.5 mm)	0.35" (8.9 mm)
Minimum Bend Radius.....	2.8" (70 mm)	3.5" (89 mm)
• Sonde.....	512 Hz, FleXmitter®	512 Hz, FleXmitter®

## ORDER INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT	
			(lb.)	(kg)
63658	rM200A	Reel, SeeSnake rM200A w/D2A Drum, TruSense	37.0	16.7
63663	rM200B	Reel, SeeSnake rM200B w/D2B Drum, TruSense	40.2	18.2
70758	D2A	Drum, rM200 D2A, TruSense	16.3	7.4
70763	D2B	Drum, rM200 D2B, TruSense	19.2	8.7



**rM200 D2A Drum**  
Catalog No. 70758



**rM200 D2B Drum**  
Catalog No. 70763



Scan for more information on HQx Live

**RIDGID.COM/seesnake**